

Ka-98H



TECHNICAL SPECIFICATIONS

The iNetVu® Ka-98H Drive-Away Antenna is a 98 cm auto-acquire satellite antenna system which can be mounted on the roof of a vehicle for direct broadband access over any configured satellite. The system works seamlessly with the iNetVu® 7024C Controller providing fast satellite acquisition within minutes, anytime anywhere.



Features

- One-Piece high surface accuracy, offset feed, steel reflector
- Heavy duty feed arm capable of supporting up to 5kg (10 lbs) RF Electronics (LNB & BUC) or transceiver
- Designed to work with the iNetVu® 7024C Controller
- Works seamlessly with the world's most popular commercially available Ka modems and services
- 2 Axis motorization
- Supports manual control when required
- One button, auto-pointing controller acquires any Ka-band satellite within 2 minutes
- Locates satellites using the most advanced satellite acquisition methods
- Supports Skyware Global 98 cm Ka antenna
- Works with HNS Spaceway (NA), YAHSAT (MENA) and Avanti (Europe)
- Standard 2 year warranty

Application Versatility

If you operate in Ka-band, the Ka-98H system is easily configured to provide instant access to satellite communications for any application that requires reliable and/or remote connectivity in a rugged environment. Ideally suited for industries such as Oil & Gas Exploration, Military Communications, Disaster Management, SNG, Emergency Communications Backup, Cellular Backhaul and many others.



www.melcom.co.uk
+44 (0) 1932 565544

Specifications are subject to change

October 2012

Ka-98H

iNetVu®

by C-COM Satellite Systems Inc.

TECHNICAL SPECIFICATIONS

Mechanical

Reflector	98 cm Elliptical Antenna, Offset feed
Mount Geometry	Elevation over Azimuth
Deployment Sensors	GPS antenna Compass $\pm 2^\circ$ Tilt sensor ± 0.1
Azimuth	Full 360° in overlapping 200° sectors
Elevation	0 - 90°
Elevation Deploy Speed	Variable 2°/sec typ.
Azimuth Deploy Speed	Variable 15°/sec Max., 10°/sec typ.
Peaking Speed	0.1°/sec

Environmental

Survival	
Wind Deployed	160 km/h (100 mph)
Wind Stowed	225 km/h (140 mph)
Temperature	-40°C to 65°C (-40°F to 150°F)
Operational	
Wind	72 km/h (45 mph)
Temperature	-30°C to 55°C (-22°F to 130°F)

Electrical

Rx & Tx Cables	2 RG6 cables - 10 m (33 ft) each	
Control Cables		
Standard	10 m (33 ft) Ext. Cable	
Optional	up to 60 m (200 ft) available	
	Receive	Transmit
Frequency (GHz)	19.20 - 20.20	29.50 - 30.00
Feed Interface (Circular)	RG6	RG6
Midband Gain (± 0.2 dBi)	43.50 @ 19.75 GHz	46.60 @ 29.75 GHz
Antenna Noise Temp. (K)	30° EL = 62 Max.	
Sidelobe Envelope, Co-Pol (dBi)		
100 λ / D < θ < 20°	29 - 25 Log θ	
20° < θ < 26.3°	-3.5	
26.3° < θ < 48°	32-25 Log θ	
48° < θ < 180°	-10 (typical)	
Cross-Polarization	> -24 dB	> -22 dB
VSWR	1.3:1	

RF Interface

Radio Mounting	Feed Arm
Coaxial	RG6U from Transceiver to Base Connector

Physical

Mounting Plate	L: 161 cm (63.5")	
	W: 45 cm (17.7")	
Stowed Dish Ext. Dims	L: 174.8 cm (68.8")	
	W: 100 cm (39.5")	
	H: 29 cm (11.5")	
Max. Deployed Height	151 cm (59.5")	
Weight	54 kg (119 lbs)	

Motors

Electrical Interface	24VDC	8 Amp (Max.)
----------------------	-------	--------------

Shipping Weights & Dimensions

Crate: 183 cm x 109 cm x 66 cm (72" x 43" x 26"), 52 kg (115 lbs)
Mount: 54 kg (119 lbs)
7024C Controller: 6 kg (13 lbs)
Cables: 5 kg (11 lbs)

Total weight: 117 kg (258 lbs)

melcom

www.melcom.co.uk
+44 (0) 1932 565544

Specifications are subject to change

October 2012