

EL940

Satellite IP Receiver

Elevation Product Family

ELEVATION

Description

The EL940 is a high performance professional satellite IP receiver designed for the reception of IP traffic transmitted over satellite in compliance with the DVB-S, DVB-DSNG or DVB-S2 standards. The EL940 connects directly to terrestrial IP network infrastructures via a single auto-switching Gigabit Ethernet interface. The receiver demodulates, restores and filters the data received from the satellite at rates of up to 154Mbit/s.

The EL940 comes with a single, fixed hardware configuration optimized for applications that requires a low initial investment without compromising on performance. It is ideally suited for point-to-multipoint applications, such as content distribution.

The PC architecture and the Linux operating system of the EL940 allows to integrate data processing software, such as Newtec's Tellitec IP software, directly on the unit (this integration may modify the performance of the device).

Key features

- DVB-S2 and DVB-DSNG/S compliant
- QPSK, 8PSK, 16APSK and 32APSK
- Multistream and VCM support
- Compatible with MPE and XPE encapsulation
- IP reception up to 154 Mbit/s
- Auto-switching GbE interface
- Linux-based PC architecture
- LNB control

Main advantages

- Cost-effective design for a low initial investment
- Full compatibility with the DVB-S/S2 standard for a guaranteed interoperability
- Highest service availability due to stable operation and robust build
- Advanced features for a maximum data throughput and operational flexibility
- Ideally suited for star topology
- Possible integration with data processing software

Applications

The IP receiver can be used in both bidirectional applications and in unidirectional applications.

- Content distribution: digital cinema, digital signage
- Primary distribution of IPTV
- IP trunking
- Corporate networking
- DSNG IP Applications

Related products

EL170 Satellite IP modulator
EL178 High Speed Satellite IP modulator
EL470 Satellite IP modem
EL478 High Speed Satellite IP modem
EL970 Satellite IP demodulator
EL978 High Speed IP Satellite Demodulator
EL8x0 Protocol Enhancement Proxy appliances

TL100 TELLINET: IP traffic enhancement and security software
TL200 TELLICAST: reliable IP multicast software
DVB-S2 link calculator (free download on www.newtec.eu)

Related Documents

White paper optimization of satellite capacity
Care Pack Brochure
Reference cases



Newtec
SHAPING THE FUTURE OF SATELLITE COMMUNICATIONS

www.newtec.eu

R12/09.2010

Specifications – EL940^(R8)

Input interface

L-band input (dual input)

- Connector 2 x F-type (F), 75 ohms
- Return loss > 7 dB
- Level -65/-25dBm
- Frequency 950 - 2150 MHz
- Adjacent signal < (Co+7) dBm/Hz
where Co = signal level density

LNB power and control

- max. current 350 mA (on selected L-band input)
- voltage 11.5-14 V (vertical polarization), 16-19 V (horizontal polarization) & additional 22 kHz $\pm$ 4 kHz (band selection according to universal LNB for ASTRA satellites) & DiSEqC command transmission (DVB-S only)

Demodulation

Baud rate range

- DVB-S/DSNG: 1-45 Mbaud
- DVB-S2 Q/8PSK, 16APSK: 0.256 -45 Mbaud
- DVB-S2 32APSK: 1 - 30 Mbaud (with option AL-15)

Supported modulation and coding types

- DVB-S/DSNG:
Outer/Innner FEC: Reed Solomon /Viterbi
MODCODs:
QPSK: 1/2, 2/3, 3/4, 5/6, 7/8
8PSK: 2/3, 5/6, 8/9
16QAM: 3/4, 7/8
- DVB-S2:
Outer/Inner FEC: BCH/ LDPC
MODCODs:
QPSK: 1/4, 1/3, 2/5, 1/2, 3/5, 2/3, 3/4, 4/5, 5/6, 8/9, 9/10
8PSK: 3/5, 2/3, 3/4, 5/6, 8/9, 9/10
16APSK: 2/3, 3/4, 4/5, 5/6, 8/9, 9/10
32APSK: 3/4, 4/5, 5/6, 8/9, 9/10
- Support of DVB-S2 Variable Coding and Modulation (VCM) mode

Performance

DVB-S2 performances at PER 1E-5

	Short Frames	Normal Frames
	< 15 Mbaud	< 45 Mbaud
Config	Es/No	Es/No
QPSK- 1/3	-0.6	-0.7
QPSK- 2/5	0.4	0.2
QPSK- 1/2	1	1.4
QPSK- 3/5	3.1	2.8
QPSK- 2/3	3.8	3.6
QPSK- 3/4	4.5	4.3
QPSK- 4/5	5.1	5.1
QPSK- 5/6	5.8	5.5
QPSK- 8/9	6.7	6.6
QPSK- 9/10	-	6.7
8PSK- 3/5	6.5	6.3
8PSK- 2/3	7.4	7.1
8PSK- 3/4	8.6	8.4
8PSK- 5/6	10.2	9.7
8PSK- 8/9	11.4	11.1
8PSK- 9/10	-	11.3
16APSK- 2/3	9.9	9.6
16APSK- 3/4	10.9	10.5
16APSK- 4/5	11.6	11.5
16APSK- 5/6	12.4	12.1
16APSK- 8/9	13.6	13.3
16APSK- 9/10	-	13.6
32APSK- 3/4	-	13.6
32APSK- 4/5	-	14.5
32APSK- 5/6	-	14.9
32APSK- 8/9	-	16.1
32APSK- 9/10	-	16.5

DVB DSNG/S performances
at BER 1E-7 after RS

	< 20 Mbaud	> 20 Mbaud
Config	Es/No	Es/No
QPSK- 1/2	3.9	3.9
QPSK- 2/3	4.4	4.5
QPSK- 3/4	4.9	5.1
QPSK- 5/6	5.4	5.8
QPSK- 7/8	5.8	6.4
8PSK- 2/3	6.3	6.5
8PSK- 5/6	8.3	8.8
8PSK- 8/9	8.8	9.8
16QAM - 3/4	8.4	8.6
16 QAM- 7/8	10.1	11.1

Supported frame length

- DVB-S/DSNG 188 byte
- DVB-S2 Short Frames 16200 bit
- DVB-S2 Normal Frames 64800 bit

Data Processing

- Maximum rate: 154 Mbit/s or 200,000 packets per second
- Supported data encapsulation protocol:
Multi Protocol Encapsulation (MPE) (EN 301 192 V1.2.1).
Extended Performance Encapsulation (XPE)
 - Newtec's highly efficient encapsulation protocol for the encapsulation of Ethernet/IP frames in DVB-S2 Base-Band frames
- Data filtering:
 - 1 stream in DVB-S2 Multistream
 - up to 256 configurable PID filters
 - one air MAC address filter

Output interface

Ethernet interface

- Dual auto-switching 10/100/1000 Base-T Ethernet interface

Generic

Monitor & Control

- Web based GUI
- Management via IP interface over Ethernet (RMCP and/or SNMPv2c)
- Key monitor parameters available locally on front panel
- Device setup available through the front panel
- Real time clock
- Persistent memory for configuration storage

Physical

- Very compact: 1RU, width: 19", depth: 14", 6kg
- Power supply: 90-130 & 180-260 Vac, 60VA
- Temperature: - Operational: 5 to 35°C
- Storage: -40 to +70°C
- Humidity: 10% to 90% non-condensing
- CE label

Ordering information

EL940 IP SATELLITE RECEIVER		Order n°
Default configuration		
DVB-S/DVB-DSNG-DVB-S2 IP receiver with GbE interface, MPE & XPE decapsulator, Multistream, VCM, L-band (950 - 2150 MHz) input, SNMP Modulation & Baud rate: DVB-S/DSNG/DVB-S2 Q/8PSK-16APSK-16QAM 45Mbaud		EL940
Configuration options		
Category		Max. 1 option per category
Modulation & Baud rate	QPSK-8PSK-16APSK-16QAM 45Mbaud	Default
	Q/8PSK-16APSK-16QAM 45Mbaud, 32APSK 30Mbaud *	AL-15
Additional options		
Category		Max. 1 option per category
Rack mount assembly Sliding rails		GM-01
Services		
Category		
Assistance	Care Pack Basic	GA-06
	Care Pack Extended	GA-07

* upgradeable via license key

Europe

Tel: +32 3 780 65 00

Fax: +32 3 780 65 49

North-America

Tel: +1 203 323-0042

Fax: +1 203 323-8406

South-America

Tel: +55 11 2092 6220

Fax: +55 11 2093 3756

Asia-Pacific

Tel: +65 6777 22 08

Fax: +65 6777 08 87

China

Tel: +86 10-823 18 730

Fax: +86 10-823 18 731

MENA

Tel: +971 4 390 18 78

Fax: +971 4 368 67 68